



Provide the right Temperature ...

... WITH THERMOSTATIC CABINETS FOR OxiTop®

Provide the right temperature

- Incubation conforming to standards
- Suited for BOD, OECD 301F, soil respiration, anaerobic degradation
- Temperature adjustable in steps of 1 K between 10° and 40 °C
- Eco-friendly refrigerant R600a



TS 608-G/2i

The new WTW® thermostatic cabinets are available in three sizes and different variants.

Note: The necessary temperature constancy will only be achieved in combination with the samples!

TS 608/2i

Compact thermostatic cabinet for up to two OxiTop® IS 12 stirring platforms. It is easy to integrate into the working environment and perfectly suited for standard applications. It has two internal plugs for connecting stirring platforms.

TS 608-G/2i

As above but with a door made of insulation glass. Allows visual checking of the OxiTop® heads without opening the door.

TS 608/4i

Thermostatic cabinet for extensive sample processing. Capable of simultaneous measurement of up to four IS 12 stirring platforms. It has four internal plugs for connecting stirring platforms.

TS 608-G/4i

As TS 608/4i but with a door made of insulation glass. Allows visual checking of the OxiTop® heads without opening the door.

TS 1008i

A thermostatic cabinet for particular applications. With extra space for special vessels e.g. biogas or soil respiration measurement. It has four internal plugs for connecting stirring platforms.

Technical data and ordering information

Model	TS 608/2i	TS 608-G/2i	TS 608/4i	TS 608-G/4i	TS 1008i
Order No.	208450	208452	208454	208456	208458
Volumen (l)	180	180	360	360	500
Outer dimensions (mm)					
H	850	850	1640	1640	1640
W	600	600	600	600	750
D	600	600	610	610	730
Inner dimensions (mm)					
H	702	702	1452	1452	1452
W	513	513	470	470	600
D	441	441	440	440	560
Net weight (kg)	34	43	53	69	69
Control range	10 °C ... 40 °C				
Increment	1 K				
Temperature stability	±0,5 K				
Max. power consumption (W)	160	320	380	380	380
Internal sockets	2	2	4	4	4

